

MDM3310 SATELLITE MODEM

The MDM3310 offers cost-effective satellite connectivity for a wide variety of professional applications on the Newtec Dialog platform.



Key Features

- High concurrent rates up to 100/25 Mbps
- Embedded TCP acceleration and encryption (not export controlled)
- Multilevel QoS with seven QoS Classes
- Low jitter for real time applications
- DNS Cache/Relay
- Versatile IP routing and addressing
- Support of IPv4 and IPv6
- Multiple virtual networks behind the modem
- DVB-S2X forward
- MF-TDMA 4CPM with Adaptive Return Link
- Mx-DMA HRC return with AUPC and ACM
- DVB-S2X return with ACM

Markets

- Enterprise/SME
- Trunking
- Cellular backhaul
- Government and defense
- Broadcast
- Offshore and maritime

Applications

- Internet/Intranet access
- VoIP telephony (SIP, H.323, ...)
- 2G/3G/4G cellular backhauling
- Backbone connections, fiber restoration
- FNG/SNG live and file contribution

Main Advantages

- High throughput upstream and downstream capabilities
- 500 Mbaud DVB-S2X forward
- MF-TDMA, Mx-DMA and SCPC return link
- VL-SNR support for extended availability and PSD restricted applications
- OpenAMIP and GXT file support for mobility
- The most optimal modulation and bandwidth allocation while guaranteeing the highest efficiency and availability
- Easy to use multilingual web GUI for installation, diagnostics and troubleshooting

MDM3310 on the Newtec Dialog® Platform

The Newtec MDM3310 Satellite Modem is a two-way, high throughput VSAT modem supporting a wide range of IP Services including Internet/ Intranet access, VoIP, enterprise connectivity, backbones for backhauling, contribution and multicasting services. Its ease of installation and high performance modulation techniques enable network operators to offer various bandwidth intensive services in a cost-effective way.

Return Link Technology Flexibility for Tailored Services

For the return channel, a choice can be made between three different return technologies depending on the type of application. The modem supports DVB-S2X SCPC in the return, which allows for highly efficient, medium to very high rate dedicated return bandwidth, for applications such as high speed IP backbones, cellular backhauling, trunking, maritime, mobility and file/video contribution.

The MF-TDMA mode enables low rate overbooked and bursty traffic profiles for inactive sites in business continuity networks or for always on connectivity in occasional use networks.

The third mode, Mx-DMA®, combines the best of both worlds and fills the gap between MF-TDMA and SCPC.

With Newtec's Mx-DMA, satellite bandwidth is allocated dynamically in real-time depending on traffic demand, Quality of Service (QoS) profiles and link conditions. Changes are seamless without packet loss or additional jitter.

This allows services with continuously changing rates as with MFTDMA, but at SCPC efficiency. Mx-DMA allows network operators to deploy anything ranging from dedicated to low-to-medium overbooked services at any given time at minimum space capacity cost.

MDM3310 SATELLITE MODEM



Satellite Link Interface

FORWARD CARRIER (RX)

- Standard: DVB-S2/DVB-S2X
 - Modulation: QPSK, 8PSK, 16APSK, 32APSK, 64APSK
 - 49 MODCODs (normal frames):
 - QPSK: from 1/4 to 9/10
 - 8PSK: from 3/5 to 9/10
 - 16APSK: from 26/45 to 9/10
 - 32APSK: from 32/45 to 9/10
 - 64APSK: from 11/15 to 5/6
 - 11 linear MODCODs (normal frames):
 - 8APSK-L: 5/9; 26/45
 - 16APSK-L: from 1/2 to 2/3
 - 32APSK-L: 2/3
 - 64APSK-L: 32/45
 - 41 MODCODs (short frames):
 - QPSK: from 11/45 to 8/9
 - 8PSK: from 7/15 to 8/9
 - 16APSK: from 7/15 to 8/9
 - 32APSK: from 2/3 to 8/9
- Roll-off: 5, 10, 15, 20, 25 and 35%
- Symbol rate: 1 Mbaud to 500 Mbaud

RETURN CARRIER (TX) :

- MF-TDMA mode
 - Modulation Scheme 4CPM (Quaternary Continuous Phase Modulation)
 - Channel bandwidth 128, 192, 256, 384, 512, 768, 1024, 1536, 2048, 2560, 3072, 3584, 4096, 6144, 8192 kHz
 - MODCODs 0, 1, 2, 3, 4, 5
- Mx-DMA mode
 - Modulation Scheme HRC
 - Modulation QPSK up-to 32APSK with 50 MODCODs
 - VL-SNR spreading 2 – 12 on 10 MODCODs
 - Roll-off 5%
 - Symbol rate 32 kbaud - 20 Mbaud
- SCPC mode
 - Modulation scheme S2 Ext
 - Modulation QPSK – 64APSK
 - Roll-off 5, 10, 15, 20, 25 and 35%
 - Symbol rate 1-40 Mbaud

Modem Interfaces

TX INTERFACE

- Frequency 950 - 2400 MHz
- Connector F-Type - 75 Ohm
- TX level -55 dBm to +5 dBm
- BUC power supply 24VDC, 4A/48V, 3.5A
- BUC reference 10 MHz, other frequencies as hardware option
- BUC reference level +3 dBm (+/- 2 dB)

RX INTERFACE (RX1/RX2)

- Frequency 950 – 2150 MHz
- Connector F-Type - 75 Ohm
- RX level -65 to -25 dBm
- LNB power supply 13/18VDC, 500mA
- Polarization selection power supply voltage
- LNB LO selection 22 kHz on/off

DATA INTERFACE

- Local Area Connection (LAN) 100/1000TX (4/2 X RJ-45, auto MDI/MDIX)

MANAGEMENT INTERFACE

- Local Area Connection (LAN) 100/1000TX (2 X RJ-45, auto MDI/MDIX)

FUTURE USE

- USB (future use) USB 2.0
- Mass storage option (future use) MicroSD cards

Management

MULTILINGUAL WEB GUI

- Web-based multilingual GUI: no installation of client software required

- Supported web browsers: Internet Explorer, Mozilla Firefox, Google Chrome, Safari
- Management web GUI accessible via configurable management IP address

ANTENNA CONTROL

- OpenAMIP support
- SNMP
 - The modem support SNMPv2 for modem performance management.

Performance

LAYER 3 - UNICAST TRAFFIC

- Max TCP receive: 125 Mbps
- Max TCP transmit: 70 Mbps
- Concurrent TCP: 100/25 Mbps
- Max UDP receive: 150 Mbps
- Max UDP transmit: 80 Mbps
- Number of TCP connections: 24.000

LAYER 3 - MULTICAST

- Max receive: 200 Mbps
- Max transmit: 85 Mbps
- Max concurrent receive multicasts: 10
- Max concurrent transmit multicasts: 4

PPS

- RX + TX: 90 kPPS

Diagnostics & Configuration

- Self-test on management GUI for end-user and operator troubleshooting including diagnostics for support case reporting.
- Automatic software upgrades via satellite

Mechanical & Environment

- Housing (W x H x D) 220 x 40 x 330 mm
- Weight 1.7 kg
- Operating Temperature 0 to 55°C
- Humidity 5% - 95% non-condensing
- Storage Temperature -30 to 60°C

Power Supply

- Modem: 48 Vdc, 4 Amps input
- Adapter AC, 50Hz/220-260V and 60Hz/100-130V -48 Vdc
- Modem power consumption: 60W maximum

Standards and Protocols

STANDARDS

Satellite Interface

- EN 302307-1 DVB-S2
- EN 302307-2 DVB-S2X
- EN 301 428 V1.3.1 (2006-02) Ku-band VSAT spectrum usage
- EN 301 459 V1.4.1 (2006-02) Ka-band VSAT spectrum usage
- EN 301 443 C-band VSAT spectrum usage

EMC

- ETSI EN 301 489-1 V1.6.1 (2005-09)
- ETSI EN 301 489-12 V1.2.1 (2003-05)
- ICES-003 Issue 4 (2004)
- FCC: title 47 of the CFR: 2008 part 15(b)

Certification

- Safety EN 60950-1 second edition
- RoHS 2002/95/EG directive compliant
- WEEE 2002/96/EG directive compliant
- CE CE compliant and marked
- UL UL compliant

LAN INTERFACE

- IEEE 802.3 10T Ethernet
- IEEE 802.3u 100TX Ethernet
- IEEE 802.2ab 1000TX Ethernet
- IEEE 802.1q VLANs

PROTOCOLS

- Terminal Authentication, UDP, IP, IPv6, ICMP, TCP, ARP, FTP, DHCP, IP forwarding, Diffserv, DNS, IGMPv1/2



Communicate. Anywhere.

sales@networkinv.com

CA: +1.403.287.5000
US: +1.954.973.3100
UK: +44.20.8286.6768
SE: +46.8.7652670

NL: +31.40.295.3001
SG: +65.6274.0811
AU: +61.1300.140.150
SA: +27.72.062.3047

www.networkinv.com

Americas
Canada
United States

Asia/Pacific
Singapore
Australia

Europe
United Kingdom
Sweden
Netherlands

Africa
South Africa