EXPLORER 727

Comms-on-the-move Inmarsat BGAN terminal

2013 Data Sheet

The most important thing we build is trust

66



₿Ś₩2690

EXPLORER 727

Comms-on-the-move BGAN terminal

Comprehensive communcation hub for vehicles

EXPLORER 727 is a high-speed, vehicular broadband system. It consists of three fully integrated units – a transceiver, an IP handset and a roof mountable antenna.

Live media broadcast, defense or humanitarian operations requires communication equipment that you can always rely on. With EXPLORER 727 you get the most comprehensive and best in class Mobile Communication Hub.



Specifications Dimensions Transceiver H / W / D: 42.5 / 231 / 273 mm 1 67 / 9 72 / 10 63 inches Antenna H / W: 152 / Ø477 mm 6.3 / Ø18.76 inches Weight 6 kg / 13.2 lbs Antenna: Transceiver: 2.5 kg / 5.5 lbs **Global Services** Voice[.] 4 kbps AMBE+2 Premium voice: 3.1 kHz audio, 64 kbps Standard IP: Up to 492 kbps 32, 64, 128, 256 kbps he-move / > 5" on-the-pause) Streaming IP: BGAN X-Stream: Min. 384 kbps on-the-pause ISDN: UDI 64 kbps / RDI 56 kbps elevation > 20° on-the-mo SMS 160 characters Guaranteed service: Works above 5° elevation Inmarsat frequencies: 1525.0 - 1559.0 MHz (Rx) 1626.5 - 1660.5 MHz (Tx) Recommended antenna cable 20 dB@1.62 GHz & Cable loss max / min: 1Ω DC loop resistance 3 dB @ 36 MHz / 4 dB @ 54 MHz



High-speed broadband on-the-Move

The antenna automatically tracks satellite positions enabling high-speed connectivity while on-the-move. Simultaneous 432 kbps data and phone calls – even at speeds in excess of 200 km/h.

Mobile Communication

Place the antenna on the roof of your vehicle to turn it into a complete mobile communication hub. Provides access to the internet and phone networks instantly.

General

| User Interface: | Power On/Off button. DC power input connector with Remote on/off and locking mechanism. Status LEDs for Power, Tran- sceiver, Antenna, and Messages. Thrane & Thrane web interface. Factory default reset |
|-----------------|---|
| Languages: | UK, FR, DE, ES, RU and CN |
| Approvals: | CE, GMPCS, FCC Inmarsat Land Class 10 Type Approval (Vehicular) |
| | |

Interfaces

2 x Analogue RJ-11 phone/fax interfaces

| 4 x LAN interfaces | |
|--------------------|---------------------------------|
| Connector type: | RJ-45 |
| | Power over Ethernet (PoE) |
| Data rate: | 10/100 Mbps |
| Max. cable length: | 100m / 328ft (Cat5 UTP) |
| Standard: | ISO/IEC 8877:1992 and |
| | IEEE 802.3 (1998 edition) |
| 1 x ISDN interface | |
| Connector type: | RJ-45 |
| I/O connector: | 5 pin general purpose I/O |
| Antenna Connector: | Transceiver, TNC-Socket, Female |
| | Antenna, TNC-Socket, Female |
| | |

BGAN SIM-Card slot

Environmental conditions

| Temperature | | | | |
|--------------------|-----------------------------|--|--|--|
| Operational: | -25 to +55°C / -13 to 131°F | | | |
| Survival: | -40 to +80°C / -40 to 176°F | | | |
| Storage: | -40 to +85°C / -40 to 185°F | | | |
| Relative humidity: | 95% non-condensing | | | |
| | at +40°C / +104°F | | | |

Middle East/Africa

Kabul, Afghanistan

Djibouti

Asia/Pacific

Singapore

Australia

Water and dust (IP-rating)

Transceiver: IP31 Antenna: IP56

Americas

Calgary, AB, Canada Fort Lauderdale, FL, USA

Europe The Netherlands London, UK

COBHAM

Live streaming - or store-and-forward

Facilitates both live streaming and store-andforward and enables direct transmissions from the hot spots of the world. Utilize the highest streaming rates available on BGAN with BGAN X-Stream when the terminal is standing still (on-the-pause).

Power

| DC input range: | 10.5-32VDC |
|-----------------|------------|
| | |

| Power | (max)@10.5-32V.: | 150W |
|-------|------------------|------|
|-------|------------------|------|

(incl. antenna & PoE output)

Other features

Telephone Functionality

Phone book, message indication, restricted dialing and traffic logging.

Set-up and Router Functionality

Webserver, Built-in NAT Router, Admin control (password protected), DHCP, Network Management, Remote Management, SIP Server, Point-to-Point Protocol over Ethernet (PPPoE), Power over Ethernet (PoE)

Package

EXPLORER 727 transceiver EXPLORER 727 tracking antenna Antenna cable, coax w/ TNC plug (2.7m & 8m / 8.8ft & 26ft) Standard ethernet cable (5m / 16.4ft) 24V DC input cable (6m / 19.7ft) with 5 additional wires for I/O connectors Thrane IP handset w/ cradle & coiled cable Antenna mounting kit (fixed / rail) Getting started kit: Quick start guide, CD with manuals

Product number

| roddoc manno. | |
|---------------|---------------------------------------|
| 403722A-20000 | EXPLORER 727 System, white antenna |
| 403722A-00700 | EXPLORER 727 System, |
| | desert sand antenna |
| 403722A-20010 | EXPLORER 727 System, |
| | 19" rack version, white antenna |
| 403722A-00710 | EXPLORER 727 System, |
| | 19" rack version, desert sand antenna |
| | |

www.networkinv.com

sales@networkinv.com

US: +1.954.973.3100 CA: +1.403.287.5000 EU: +31.40.295.3001 UK: +44.20.8286.6768 SG: +65.6274.0811 AU: +61.466.896.386