

## BEAM PotsDock9555

### Key Features PotsDOCK 9555 Cradle

- Securely holds 9555 handset
- Robust design and construction
- Charges 9555 handset ready for use
- Integrated antenna connection
- Integrated USB connectivity

### POTS/RJ11

- Supports standard cordless & corded telephones (5 REN)
- RJ11 can be run 600m (2000 ft) from unit
- Corded, cordless or DECT handsets
- Easily integrated to PBX system
- Ring, busy & dial tones
- Superior voice quality

### Installation

- Supports 9 - 32V DC power input
- Flexible installation w/universal mount, also suitable for wall
- Supplied with 110 - 240V AC Plug pack
- Handset always charged ready for use

### Integrated Bluetooth®

- Bluetooth® in-built in cradle
- Supports Bluetooth® voice & data accessories

### In-Built Ringer

- In-built ringer for enhanced ring indication

### Voice, Data, SMS, SBD

- Supports all Iridium voice, data, SMS & SBD services
- Access to prepaid, post paid & crew calling

### Privacy Handset

- Supports optional Beam privacy handset
- Auto sensing answer/hang-up intelligence

### Tracking/GPS

- Tracking & alert monitoring capable
- Periodic position reports or remotely polled
- Triggered position status message
- In-built GPS engine
- Interfaces to Beam's LeoTRAK- online



PotsDOCK 9555 is an intelligent compact docking station specifically designed for the Iridium 9555 satellite handset. PotsDOCK allows the 9555 handset to be used in a wide variety of applications using an intelligent RJ11/POTS connectivity that supports standard corded, cordless or DECT handsets, or alternatively interfaced with a PBX system.

PotsDOCK also has an in-built Bluetooth® module for voice and data connectivity along with an intelligent tracking and alert reporting system that can be easily configured to support periodic polling or emergency alert reporting.

The cleverly designed PotsDOCK cradle simply and securely docks the Iridium 9555 handset into place ready for use and fully integrates antenna, power and data connectivity into a single streamline unit.

The 9555 handset is easily inserted and removed by the press of a button on the top of the dock, making it very easy for use out of the dock at anytime.

PotsDOCK also supports the use of an optional compact Beam Privacy Handset that can be located next to the PotsDOCK for added convenience if required.

### Tracking / Alert Monitoring

PotsDOCK has an in-built GPS module that can provide simple tracking, monitoring and alert management in various applications within various types of vehicles, vessels or fixed site locations.

The GPS provides pinpoint accuracy and enables tracking worldwide. Tracking and alert messages can be sent via SMS or Short Burst Data, if provisioned on the handset.

PotsDOCK's tracking and alert messages can be simply sent to Beam's LeoTRAK-Online or any other tracking application, SMS or email address as required.

# BEAM PotsDock9555



Alert/Alarm messages can be activated on the PotsDOCK using the two button press on the front of the cradle or alternatively an additional alert button or other trigger can be connected to the unit. Once configured the alert system is always on and will generate an alert message to the preset destination once triggered. Alerts can be triggered to continually send until the alert is cleared either remotely or locally on the PotsDOCK unit.

Tracking messages can be sent from the PotsDOCK via the following means:

1. Periodic position reporting, preset during configuration of the terminal
2. Upon an alert being activated via the Alert button on the cradle or connected alert button
3. A current location position can be sent at any time by pressing the Track button on the front of the PotsDOCK

Iridium Network		
9555 Handset 1616 - 1625 MHz		
Compressed Data 10 - 12 kbps		
Voice/Data Modulation 2.4 kbps		
Power Specifications		
Power input voltage 9 - 32 V DC, 2A max		
Power Consumption at 12V DC		
Stand-by (when battery charged) - incl handset & RJ11	1.1W (90mA @ 12Vin)	
Transmit - incl handset & RJ11	6W (0,5A @ 12Vin)	
GPS MODULE		
Channels	14 tracking, 51 Channel Acquiring	
Update Rate	1Hz	
Accuracy	Position 2.5mCEP, Velocity 0.1m/s, Timing 300ns	
Acquisition TTFF	Cold 29sec, Hot 1sec	
Sensitivity	-161 dBm	
Operational Limits	Altitude 18000m , Velocity 515m/s	
Dynamics	4G	
Physical Specifications	Unit Only	Packed
Dimensions - mm	200 x 75 x 65	325 x 140 x 88
Dimensions - inches	7.9 x 3.0 x 2.7	7.2 x 5.1 x 1.0
Weight - kg	0.32	1.3
Weight - lbs	0.7	2.86
Operating Temperature	-30 to +70 °C	-22 to +158 °F
Storage Temperature	-40 to +85 °C	-40 to 185 °F
Humidity	93% non condensing	
I/O Alarm / Alert		
Alert Button	In-built on PotsDOCK - 2 Key Press	
1 x Alarm Loop	Bare Wire - "Normally Closed" Loop IN to OUT Up to 500m cable run/multi buttons	
Track	Inbuilt - single key press	

Connectors/Interfaces	
POTS/RJ11	RJ11/2-wire, complex or 600 Ω, 5REN, 600m adjustable dial/busy tones/ frequency, adaptive Z
Iridium - Antenna	Fixed Cable to TNC-Female
GPS-Antenna	Fixed Cable to SMA-Female
9-32	V DC 4-way microFit (AC/DC adator, or DC lead)
Privacy Handset Port	4 pole 3.5mm jack
Data Port	USB Mini Base of Dock
Bluetooth® Voice / Data	Inbuilt module/antenna, class 1 (up to 300m) Bluetooth® system 2.0v+EDR, CE
Buttons/LEDs	
Bluetooth®	Blue/Orange
Alert	Red/Orange
Mute/Ringer	Red
Backlight	White LED
Handset Release	Top of Cradle, No LED
Certifications	
Iridium Approved	
Electrical Safety	
EMC Compliance	
CE Compliance	
RoHS	
CTick	
Independant Aeronautical certification MUST be gained prior installation	
Kit Contents	
Beam PotsDOCK Cradle	
Universal Mounting Bracket (RAM)	
110 - 240V AC Plug Pack	
9 - 32V DC Power Cable	
Quick Start Guide	
User Manual	



sales@networkinv.com

CA: +1.403.287.5000  
 US: +1.281.485.8800  
 UK: +44.20.8286.6768  
 SE: +46.8.7652670

NL: +31.40.295.3001  
 SG: +65.6274.0811  
 AU: +613.9602.2002  
 ZA: +27.72.062.3047

www.networkinv.com

**Americas**  
 Canada  
 United States

**Asia/Pacific**  
 Singapore  
 Australia

**Europe**  
 United Kingdom  
 Sweden  
 Netherlands

**Africa**  
 South Africa